

Safety Data Sheet

1-Butanol

CAROLINA[®]
www.carolina.com

Section 1

Product Description

Product Name: 1-Butanol
Recommended Use: Science education applications
Synonyms: N-Butyl Alcohol, Butyl Alcohol, N-Butanol, Butan-1-ol, 1-Hydroxybutane
Distributor: Carolina Biological Supply Company
2700 York Road, Burlington, NC 27215
1-800-227-1150
Chemical Information: 800-227-1150 (8am-5pm (ET) M-F)
Chemtrec: 800-424-9300 (Transportation Spill Response 24 hours)

Section 2

Hazard Identification

Classification of the chemical in accordance with paragraph (d) of §1910.1200;

DANGER



Flammable liquid and vapor. Harmful if swallowed. Causes skin irritation. Causes serious eye damage. May cause respiratory irritation. May cause drowsiness or dizziness.

GHS Classification:

Serious Eye Damage/Eye Irritation Category 1, Skin Corrosion/Irritation Category 2, Flammable Liquid Category 3, Specific Target Organ Systemic Toxicity (STOT) - Single Exposure Category 3, Acute Toxicity - Oral Category 4

Section 3

Composition / Information on Ingredients

<u>Chemical Name</u>	<u>CAS #</u>	<u>%</u>
1-Butanol	71-36-3	100

Section 4

First Aid Measures

Emergency and First Aid Procedures

Inhalation: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
Eyes: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
Skin Contact: IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. IF ON SKIN: Wash with plenty of soap and water. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash before reuse.
Ingestion: IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell.

Section 5

Firefighting Procedures

Extinguishing Media: Use dry chemical, CO2 or appropriate foam.
Fire Fighting Methods and Protection: Firefighters should wear full protective equipment and NIOSH approved self-contained breathing apparatus.
Fire and/or Explosion Hazards: Vapors may travel back to ignition source. Closed Containers exposed to heat may explode.
Hazardous Combustion Products: Carbon dioxide, Carbon monoxide

Safety Data Sheet

Section 6

Spill or Leak Procedures

Steps to Take in Case Material Is Released or Spilled:

Exposure to the spilled material may be irritating or harmful. Follow personal protective equipment recommendations found in Section 8 of this SDS. Additional precautions may be necessary based on special circumstances created by the spill including; the material spilled, the quantity of the spill, the area in which the spill occurred. Also consider the expertise of employees in the area responding to the spill.

Methods for Clean-up

Prevent the spread of any spill to minimize harm to human health and the environment if safe to do so. Wear complete and proper personal protective equipment following the recommendation of Section 8 at a minimum. Dike with suitable absorbent material like granulated clay. Gather and store in a sealed container pending a waste disposal evaluation. Shut off ignition sources; including electrical equipment and flames. Do not allow smoking in the area.

Section 7

Handling and Storage

Handling:

Keep away from heat/sparks/open flames/hot surfaces. – No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/.../ equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Avoid breathing dust/fume/gas/mist/vapors/spray. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection.

Storage:

Keep container tightly closed. Store in a well-ventilated place. Keep container tightly closed. Store locked up. Keep cool.

Storage Code:

Red - Flammables. Store in approved flammable containers. Store away from oxidizing materials.

Section 8

Protection Information

Chemical Name

1-Butanol

ACGIH

(TWA)

20 ppm TWA

(STEL)

N/A

OSHA PEL

(TWA)

100 ppm TWA; 300 mg/m³ TWA

(STEL)

N/A

Control Parameters

Engineering Measures:

Local exhaust ventilation or other engineering controls are normally required when handling or using this product to avoid overexposure.

Personal Protective Equipment (PPE):

Lab coat, apron, eye wash, safety shower.

Respiratory Protection:

Respiratory protection may be required to avoid overexposure when handling this product. General or local exhaust ventilation is the preferred means of protection. Use a respirator if general room ventilation is not available or sufficient to eliminate symptoms.

Respirator Type(s):

NIOSH approved air purifying respirator with organic vapor cartridge and HEPA filter.

Eye Protection:

Wear chemical splash goggles when handling this product. Have an eye wash station available.

Skin Protection:

Avoid skin contact by wearing chemically resistant gloves, an apron and other protective equipment depending upon conditions of use. Inspect gloves for chemical break-through and replace at regular intervals. Clean protective equipment regularly. Wash hands and other exposed areas with mild soap and water before eating, drinking, and when leaving work.

Gloves:

Nitrile, Butyl rubber, Natural rubber, Polyvinyl chloride, Neoprene

Section 9

Physical Data

Formula: C₄H₉OH

Molecular Weight: 74.12

Appearance: Colorless Liquid

Odor: Moderate Sweet Rancid

Odor Threshold: No data available

pH: No data available

Melting Point: -90 C

Boiling Point: 118 C

Flash Point: 37 C

Flammable Limits in Air: 1.45 - 11.25%

Vapor Pressure: 7 mm Hg at 25°C

Evaporation Rate (BuAc=1): 33 (ether = 1)

Vapor Density (Air=1): 2.6

Specific Gravity: 0.81

Solubility in Water: Soluble

Log Pow (calculated): 0.785

Autoignition Temperature: 343 C

Decomposition Temperature: No data available

Viscosity: 2.544 cP at 25 C

Percent Volatile by Volume: 100%

Safety Data Sheet

Section 10

Reactivity Data

Reactivity:	Not generally reactive under normal conditions.
Chemical Stability:	Stable under normal conditions.
Conditions to Avoid:	Temperatures above the high flash point of this combustible material in combination with sparks, open flames, or other sources of ignition.
Incompatible Materials:	Strong oxidizing agents, Alkali and Alkaline Metals, Halogens, Mineral acids
Hazardous Polymerization:	Will not occur

Section 11

Toxicity Data

Routes of Entry	Inhalation, ingestion, eye or skin contact.
Symptoms (Acute):	Central Nervous System Disorders, Headache, Gastrointestinal,
Delayed Effects:	Sensitivity to Light Lachrymation Central Nervous System Disorders Liver disorders Impaired Kidney Function

Acute Toxicity:				
Chemical Name	CAS Number	Oral LD50	Dermal LD50	Inhalation LC50
1-Butanol	71-36-3	Oral LD50 Rat 790 mg/kg	Not determined	INHALATION LC50 Rat 8000 PPM 4H

Carcinogenicity:				
Chemical Name	CAS Number	IARC	NTP	OSHA
No data available				

Chronic Effects:	
Mutagenicity:	No evidence of a mutagenic effect.
Teratogenicity:	No evidence of a teratogenic effect (birth defect).
Sensitization:	No evidence of a sensitization effect.
Reproductive:	No evidence of negative reproductive effects.
Target Organ Effects:	
Acute:	Central Nervous System, Kidneys, Liver
Chronic:	No data available

Section 12

Ecological Data

Overview:	This material is not expected to be harmful to the ecology.
Mobility:	This material is expected to have high mobility in soil. It absorbs weakly to most soil types.
Persistence:	Evaporation into atmosphere
Bioaccumulation:	Bioconcentration is not expected to occur.
Degradability:	No data
Other Adverse Effects:	No data

Chemical Name	CAS Number	Eco Toxicity
1-Butanol	71-36-3	96 HR LC50 PIMEPHALES PROMELAS 1730 - 1910 MG/L [STATIC] 96 HR LC50 PIMEPHALES PROMELAS 1740 MG/L [FLOW-THROUGH] 96 HR LC50 LEPOMIS MACROCHIRUS 100000 - 500000 MG/L [STATIC] 96 HR LC50 PIMEPHALES PROMELAS 1910000 MG/L [STATIC] 48 HR EC50 DAPHNIA MAGNA 1983 MG/L 48 HR EC50 DAPHNIA MAGNA 1897 - 2072 MG/L [STATIC] 96 HR EC50 DESMODESMUS SUBSPICATUS > 500 MG/L 72 HR EC50 DESMODESMUS SUBSPICATUS > 500 MG/L

Safety Data Sheet

Section 13

Disposal Information

Disposal Methods: Dispose in accordance with all applicable Federal, State and Local regulations. Always contact a permitted waste disposer (TSD) to assure compliance.

Waste Disposal Code(s): U031 - 1-Butanol

Section 14

Transport Information

Ground - DOT Proper Shipping Name:	Air - IATA Proper Shipping Name:
UN1120	UN1120
Butanols	Butanols
Class 3	Class 3
P.G. III	P.G. III

Section 15

Regulatory Information

TSCA Status: All components in this product are on the TSCA Inventory.

Chemical Name	CAS Number	§ 313 Name	§ 304 RQ	CERCLA RQ	§ 302 TPQ	CAA 112(2) TQ
1-Butanol	71-36-3	n-Butyl alcohol	No	5000 lb final RQ; 2270 kg final RQ	No	No

California Prop 65: No California Proposition 65 ingredients

Section 16

Additional Information

Revised: 03/22/2024

Replaces: 03/22/2024

Printed: 01-17-2025

The information provided in this (Material) Safety Data Sheet represents a compilation of data drawn directly from various sources available to us. Carolina Biological Supply makes no representation or guarantee as to the suitability of this information to a particular application of the substance covered in the (Material) Safety Data Sheet.

Glossary

ACGIH	American Conference of Governmental Industrial Hygienists	NTP	National Toxicology Program
CAS	Chemical Abstract Service Number	OSHA	Occupational Safety and Health Administration
CERCLA	Comprehensive Environmental Response, Compensation, and Liability Act	PEL	Permissible Exposure Limit
DOT	U.S. Department of Transportation	ppm	Parts per million
IARC	International Agency for Research on Cancer	RCRA	Resource Conservation and Recovery Act
N/A	Not Available	SARA	Superfund Amendments and Reauthorization Act
		TLV	Threshold Limit Value
		TSCA	Toxic Substances Control Act
		IDLH	Immediately dangerous to life and health